

HBT8018C-5S(T3) TRAILER PUMP HBT8018C-5S(T3) 拖泵

Advanced Hydraulic System

Differential pressure controlled, bi-directional hydraulic system. High flow, high efficiency valve system Automatically retracted pistons

Avanced Energy-saving Technology

New generation energy saving technology automatically adjusts engine power output to match the load results in fuel savings of up to 25%.

Intelligent Control System

Fault self-diagnosis technology Dedicated motion controller Emergency Override Available

Efficient Pumping System

High-efficiency pump technology High power mixing motor Large bore reversing cylinder New-type hopper

Wear-resisting Technology


G5 improved wearing part Adopt Sino-Germany high-tech materials and advanced technology to greatly improve the product performance



TECHNICAL PARAMETER

技术参数

型号 Model			HBT8018C-5S(T3)
混凝土 最大理论输送压力	低压 Low Pressure		10
Max. Delivery Pressure (theoretical)(Mpa)	High Pressure		18
混凝土 最大理论输送量	低压 Low Pressure		85
Max. Concrete Output (theoretical)(m³/h)	高压 High Pressure		50
发动机 / 电动机额定功率 Motor Rated Power (kW/rpm)			180/2200
输送缸直径 × 最大行程 Delivery Cylinder Bore (mm) × Strok (mm)			Ф200×1800
料斗容积×上料高度 Hopper Capacity (m³) × Feeding Height (mm)			0.7×1420
外形尺寸(长×宽×高) Dimension (L×W×H) (mm)			7330×2125×2685
总质量 Gross Weight (kg)			7300
最大骨料尺寸 Max. Aggregate Size (mm)	输送管径 Delivery Pipe	Ф150 mm	50
		Ф120 mm	40
类型 Type			S 阀 S-Valve
砼塌落度 Slump of Concrete (mm)			100~230



CHALLENGE THE HEIGHT OF SKY

